

PRODUCT NAME	SERIES 5000	SERIES 6000	SERIES 6100
Frame Depth	2¼"	2½"	3¾"
Configurations	Casement, Awning, Hopper, Fixed	Casement, Awning, Fixed	Casement, Awning, Fixed
Frame Types	Nail On, Panning, Equal Leg/ Comp Channel, F-Clip, Z-Bar	Nail On, Panning, Equal Leg/ Comp Channel, Low Profile	Nail On
Max Casement Size	36" x 60"	36" x 72"	48" x 96"
Max Fixed Lite Size	50 sq. ft.	60 sq. ft.	60 sq. ft.
Thermally Broken	Yes	Yes	Yes
Glazing	1" OA	1"-1½" Triple Glazed	1"-1¼" Triple Glazed
SDL	1" Flat or Beveled	1" Flat	1" Flat
TDL	2 <sup>3</sup> / <sub>8</sub> "	2½"	3 <sup>1</sup> / <sub>8</sub> "
Split Finish	No	Yes	Yes
PERFORMANCE	SERIES 5000	SERIES 6000	SERIES 6100
DP Structural Rating	PG50	PG80	PG60
NFRC Energy Rating	0.41	0.38	0.30*
STC Acoustic Rating	Up to 39	Up to 41	Up to 43*

*\*Series 6100 NFRC and STC ratings pending final test results.*

Performance based on casement window testing results. Comparison chart data subject to change without notice. Visit [allweatheraa.com](http://allweatheraa.com) for current product information and ratings.

PRODUCT NAME	SERIES 7000	SERIES 8000	SERIES 8150	SERIES 8100	SERIES 9100
Door Operation	Swing	Multi Slide	Sliding	Multi Slide	Bifold
Configurations	Inswing, Outswing	XO, OX, XXO, OXX, OXO, XOO, OOX, OXXO, OXXXXO	XO, OX, OXXO	Unlimited Flush Stacking, Corner, Pocket	Inswing, Outswing
Max Panel Size	48"x96", 42"x108", 36"x120"	70 sq. ft.	70 sq. ft.	70 sq. ft.	39" x 144"
Max Panel Width	48"	96"	96"	96"	39"
Max Panel Height	120"	144"	144"	144"	144"
Max # of Panels	2	8	4	Unlimited	16
Thermally Broken	Yes	Yes	Yes	Yes	No
Sill Options	½" Low Profile, 2¾" Sill	2" Sill	¾" Low Profile, 2" Sill	¾" Low Profile, 2" Sill, Tile Sill	½" Low Profile, 2¼" Sill
Glazing	1"-1¼" Triple Glazed	1" OA	1" OA	1" OA	15/16" OA
SDL	1" Flat	1" Flat	1" Flat	1" Flat	N/A
TDL	2½"	2½"	N/A	N/A	N/A
Split Finish	Yes	Yes	No	No	No
PERFORMANCE	SERIES 7000	SERIES 8000	SERIES 8150	SERIES 8100	SERIES 9100
DP Structural Rating	C30	C30	C35	C30	N/A
Up to .30 U Value Achievable	No	Yes	No	Yes	No
NFRC Certified	Yes	Yes	Yes	Yes	No
STC Acoustic Rating	Up to 40	Up to 34	Up to 38*	Up to 38	N/A

\*Series 8150 STC ratings pending final test results.

Performance based on 2" Sill and dual glazed testing results. Comparison chart data subject to change without notice. Visit [allweatheraa.com](http://allweatheraa.com) for current product information and ratings.