

PRODUCT NAME	SERIES 5000	SERIES 6000	SERIES 6100
Frame Depth	2¼"	2½"	3¾"
Configurations	Casement, Awning, Hopper, Fixed	Casement, Awning, Fixed	Casement, Awning, Fixed
Frame Types	Nail On, Panning, Equal Leg/ Comp Channel, F-Clip, Z-Bar	Nail On, Panning, Equal Leg/ Comp Channel, Low Profile	Nail On
Max Casement Size	36" x 60"	36" x 72"	48" x 96"
Max Fixed Lite Size	50 sq. ft.	60 sq. ft.	60 sq. ft.
Thermally Broken	Yes	Yes	Yes
Glazing	1" OA	1"-1½" Triple Glazed	1"-1¼" Triple Glazed
SDL	1" Flat or Beveled	1" Flat	1" Flat
TDL	2 ³ / ₈ "	2½"	3 ³ / ₁₆ "
Split Finish	No	Yes	Yes
PERFORMANCE	SERIES 5000	SERIES 6000	SERIES 6100
DP Structural Rating	PG50	PG80	PG60
NFRC Energy Rating	0.41	0.37	0.31*
STC Acoustic Rating	Up to 39	Up to 41	Up to 41*

*Series 6100 NFRC U-Factor of 0.24 for triple glazed casement window. Series 6100 STC ratings pending final test results.

Performance based on dual glazed casement window test results. Comparison chart data subject to change without notice. Visit allweatheraa.com for current product information and ratings.

PRODUCT NAME	SERIES 7000	SERIES 7200	SERIES 8000	SERIES 8100	SERIES 8150	SERIES 9200
Door Operation	Swing	Pivot	Multi Slide	Multi Slide	Sliding	Bifold
Configurations	Inswing, Outswing Single or Double Panel	Inswing, Outswing Single or Double Panel	XO, OX, XXO, OXX, OXO, XOO, OOX, OXXO, OXXXXO	Unlimited Flush Stacking, Corner, Pocket	XO, OX, OXO, OXXO	Inswing, Outswing Unlimited, up to 8 panels in each direction
Max Panel Size	48"x96", 42"x108", 36"x120"	60" x 144"	70 sq. ft.	70 sq. ft.	70 sq. ft.	42" x 144"
Max Panel Width	48"	60"	96"	96"	96"	42"
Max Panel Height	120"	144"	144"	144"	144"	144"
Max # of Panels	2	2	8	Unlimited	4	Unlimited
Thermally Broken	Yes	Yes	Yes	Yes	Yes	Yes
Sill Options	½" Low Profile, 2⅜" Sill	⅜" ADA Sill, No Sill	2" Sill	¾" Low Profile, 2" Sill, Recessed Tile Sill	¾" Low Profile, 2" Sill	¾" Recessed, 1½" Recessed, 2⅜" Sill
Glazing	1"-1¼" Triple Glazed	1¼" OA	1" OA	1" OA	1" OA	1" OA
SDL	1" Flat	⅝", ⅞" Square or Putty, 1" Flat	1" Flat	1" Flat	1" Flat	⅝", ⅞" Square or Putty, 1" Flat
TDL	2½"	3¼", 4⅝"	2⅝"	2⅝"	2⅝"	2⅝"
Split Finish	Yes	No	Yes	No	No	No
PERFORMANCE	SERIES 7000	SERIES 7200	SERIES 8000	SERIES 8100	SERIES 8150	SERIES 9200
DP Structural Rating	C30	N/A	C30	C30	C35	PG45
Up to .30 U Value Achievable	No	No	Yes	No	Yes	No
NFRC Certified	Yes	Yes	Yes	Yes	Yes	Yes
STC Acoustic Rating	Up to 40	N/A	Up to 34	Up to 38	Up to 38*	N/A

*Series 8150 STC ratings pending final test results.

Performance based on 2", 2⅜", 2⅝" Sill and dual glazed testing results. Comparison chart data subject to change without notice. Visit allweatheraa.com for current product information and ratings.